



From daily maintenance to outdoor activity.



Max air pressure

830 kPa

Air Discharge Amount

12 [200kPa] L/min

Net weight

1.7 [with BL1850B] kg



18V LXT Li-Ion Cordless Inflator

Blows up air in the tires of cars/bikes





Max air pressure

PSI / bar / kPa can be changed

Pre-set pressure stop function



LED job Light for easy operation at dark



Digital pressure gauge provides high visibility with backlight.









Valve adapters

	Car / Motorcycle	Bicycle	Road bike	Ball	Beach ball / Swim ring
Valve shape					- <u>a</u>
	American	British	French	For Balls	For Swim rings/ Beach balls
Adapter	T. Daniel		Part No. TE00000334	Part No. TE00000335	Part No. TE00000333
Maximum air pressure: kPa	(approx.) 250	(approx.) 300	(approx.) 700	(approx.) 90	50 and under
Discharge amount: L/ min (at Target pressure)		13	25	25	33
a single full battery charge: count	Car tires (215/60R16)	Bicycle tires (Size-26inch)	Road bike tires (700x23c)	Soccer balls (Size-5) 142	Beach balls (dia.30cm)

Cordless Inflator

	DMP180						
Þ	່∷- Built-in Job Light	Max Air Pressure	830 kPa (121 PSI) [8.3 bar				
	-	Air Discharge Amount	200 kPa: 12 L/min				
	Carrying Case	Hose Length	65 cm (25-1/2")				
		Dimensions (L x W x H)	w/BL1815N/BL1820B:				
			246x80x174 mm				
			(9-11/16"x3-1/8"x6-7/8")				
			w/BL1830B/BL1840B/				
			BL1850B / BL1860B:				
			266x80x174 mm				
			(10-1/2"x3-1/8"x6-7/8")				
		Net weight	1.4 - 1.7 kg (3.1 - 3.8 lbs.)				
	Standard Equipment :	British Adapter, French Adapter, Ball Adapter, Swim Ring Adapter, Battery, Charger					

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan