7.2V -1.5Ah NEW **Li-ion battery BL0715**

Use of the stick-type Li-ion battery allows for compact and lightweight tool design.















Comparison of Products

- 1. The test results depend to a great extent on the hardness of the material, etc.
- 2. Numbers in the charts below are relative values when the capacities of Conventional model is indexed at 100.

Cordless Impact Driver


Drove ø3.1x25mm wood screw into Merapi

Work Amount on a single full battery charge Makita TD022D Makita TD022D 100

Cordless Driver Drill

Drove 3.8x25mm Coarse thread screws into an SPF plate in high speed mode.

Makita DF012D 100



Cordless Impact Driver

TD022D





No Load Speed (RPM)

0 - 2,450 0 - 3,000 25 N·m (220 in·lbs) Machine screw: M3 - M8 (1/8" - 5/16") Standard bolt : M3 - M8 (1/8" - 5/16") High strength bolt : M3 - M6 (1/8" - 1/4") Coarse thread (in length): 22 - 45mm (7/8" - 1-3/4")
Fastening Bolt: 7.0 m/s²

Sound Pressure Level Sound Power Level

Vibration Level

Straight Type: 282x42x52mm(11-1/8"x1-5/8"x2-1/16") Pistol Type: 227x42x142mm (8-15/16"x1-5/8"x5-5/8")

Standard Equipment: Holster, Bit set, Battery, Charge

Cordless Driver Drill

DF012D



Reversing Mechanical 2-Speed Torque Setting 21

Built-in Job Light

Capacity No Load Speed (RPM) Max lock torque Vibration Level Sound Pressure Level ensions (L x W x H)

Steel: 5 mm (3/16") Wood: 6 mm (1/4") High: 650 Low: 200 Hard / Soft: 5.6 / 3.6 N·m (50 / 32 in.lbs.) 8 0 N·m (71 in lbs) Drilling Into Metal: 2.5 m/s² or less 70 dR(A) or less Pistol style: 218x44x142mm (8-5/8"x1-3/4"x5-5/8") Straight style: 273x44mm (10-3/4"x1-3/4") 0.53 kg (1.2 lbs.)

weight according to EPTA-Procedure 01/ver.2.1

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201703



Cordless Impact Driver TD022D Cordless Driver Drill DF012D





Battery capacity 50% up*





Fastening speed 10%UP*



High fastening torque 25_{N⋅m}

High speed (no load) 0-2,450 rpm

More work amount



Drove wood screw into Merapi**

Work Amount on a single full battery charge


ø3.1x25mm 320pcs

ø4.1×45mm

65pcs

**The test results depend to a great extent on the hardness of the material, etc.

High torque accuracy



Auto-stop clutch

The motor automatically stops at the moment when the clutch is disengaged.

Auto-stop system

Indication lamp warns user visually of battery power reduction when it reduces to a certain low level. If battery power reduces further, the motor automatically stops to prevent incomplete fastening.

More work amount



Drove wood screw into Merapi**

Work Amount on a single full battery charge

ø3.8x25mm

350pcs

ø3.8×38mm

210pcs

**The test results depend to a great extent on the hardness of the material, etc.

Common features

LED Job light Brightly illuminates a spot and the periphery by enlarging the illuminated area.







Can be used as a hand Screwdriver






Convenient for:

- driving screws in delicate places where driving with impact mechanism may damage screw or workpiece.
- making sure that screws are securely tightened at proper torque.

Compact and lightweight



- Easy handling





TD022D **0.56kg**

DF012D 0.53kg

