



# Cordless Air Compressor AC001G



**XGT**  
**40V** **Li-ion**  
**max**



Low noise

**68 dB(A)**

Tank capacity

**7.6 L**

Max Pressure

**0.93 MPa**

Lightweight Battery: BL4020-BL4080F

**11.6-12.8 kg**



# Surrounding environment-friendly machine with low noise level

**Low noise**  
**68 dB(A)**

**Rigid roll cage frame construction** minimizes the chance of damage to the motor and compression units.

**Carrying handle** with rubberized grip designed for easy transportation



**Air filter (air intake)**



**Oil-free pump design**

**Powered by 40Vmax XGT Li-Ion battery**



**BL MOTOR**

**High operating efficiency motor**

**One outlet (coupler)**

**Air tank capacity: 7.6L**  
**Max air pressure in tank: 0.93MPa**  
The cut-in pressure is 0.72MPa

## Charging Time

	Fast Charging	
	DC40RA	DC40RC
<b>BL4020</b> 2.0Ah	<b>22 min</b>	<b>30 min</b>
<b>BL4025</b> 2.5Ah	<b>28 min</b>	<b>38 min</b>
<b>*1 BL4040</b> 4.0Ah	<b>45 min</b>	<b>67 min</b>
<b>*1 BL4050F</b> 5.0Ah	<b>50 min</b>	<b>85 min</b>
<b>*1 BL4080F</b> 8.0Ah	<b>76 min</b>	<b>170 min</b>

\*1 Recommended battery

## Cordless Air Compressor AC001G

Tank	7.6 L (2 gal)
Cut-In Pressure	0.72 MPa (105 PSI)
Cut-Out Pressure	0.93 MPa (135 PSI)
Number of Outlets	1
Performance	34.0 L/min
Noise Level	68 dB(A)
Dimensions (L x W x H)	302x434x382 mm (11-7/8" x 17-1/8" x 15")
Net weight	11.6 - 12.8 kg (25.6 - 28.2 lbs.)

Battery & Charger Sold Separately

The weight does not include battery cartridge  
Items of standard equipment and specifications may vary by country or area.

**Makita Corporation**

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202209