



Predecessor Model 439mm

makita.

DJR188

316_{mm} Makita

akite



tweight

MLERE

5.0 ALTIBY COMMON



Satisfy Professional's Needs

Compact & Powerful



Ergonomically designed handle

fits your hand well, even during difficult cutting applications such as overhead application, cutting with the saw upside down, etc.



TBV NITHIUMHON	BL1815N 1.5Ah	BL1820B 2.0Ah	BL1830B 3.0Ah	BL1840B 4.0Ah	BL1850B 5.0Ah	BL1860B 6.0Ah
DC18RC Two port multi Fast Charger DC18RD	15 min	24 min	22 min	36 min	45 min	55 min
DC185D	30 min	45 min	60 min	90 min	110 min	130 min



Cordless Recipro Saw	DJR188	
 Variable Speed Brake Constant Speed Built-in Job Light Carrying Case 	Length of Stroke Strokes Per Minute (SPM) Capacity Vibration Level Sound Pressure Level Dimensions (L x W x H) Net weight Standard Equipment : Recip	20 mm (13/16") 0 - 3,000 Pipe: 130 mm (5-1/8") Wood: 255 mm (10") Cutting Boards: 15.5 m/s ² Cutting Wooden beams: 15.0 m/s ² 83 dB(A) 94 dB(A) with BL1815N / BL1820B: 316x81x203 mm (12-1/2"x3-3/16"x8") with BL1830B / BL1840B / BL1850B / BL1860B: 316x81x220 mm (12-1/2"x3-3/16"x8-5/8") 2.6 - 2.9 kg (5.7 - 6.4 lbs) ro Saw Blades, Charger, Battery

Items of standard equipment and specifications may vary by country or area. The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan